

ROLLING EVO

SEB.P | SEB.E | SEP.P | SEP.E

L'UNICO SOLLEVATORE A PEDANE SU RUOTE CON CUI SI PUÒ MOVIMENTARE UN VEICOLO

THE ONLY PLATFORM-LIFT WITH WHICH A VEHICLE CAN BE MOVED

- Le pedane multi-posizione lo rendono adatto a tutti i veicoli dalle city-car alle granturismo.
- Sistema di sicurezza antiscivolamento su tutte le pedane.
- Salita a bordo del veicolo semplice e veloce, nessun intervento dell'operatore.
- Ruote di grande diametro per agevolare la movimentazione del veicolo, un solo operatore necessario.
- Basso profilo, soltanto 10cm di ingombro in altezza.
- Utilizzabile anche con braccetti presa sotto-scocca al posto delle pedane.

- Adjustable platforms positioning makes it suitable for both city cars and GT cars.
- Anti-rolling safety system on all platforms.
- Quick and easy vehicle boarding, no manual intervention.
- Large diameter wheels to facilitate the vehicle movement, just one operator required.
- Low profile, 10cm only as minimum height.
- Can be used with under-body lifting arms in place of wheels platform.



SEP.E

Rolling Evo
con pedane e centralina

Rolling Evo with platforms
and power unit



SEP.P

Rolling Evo
con pedane e pompa

Rolling Evo with platforms
and pump

SEB.P

Rolling Evo
con braccetti e pompa

Rolling Evo with arms
and pump

**SEB.E**

Rolling Evo
con braccetti e centralina

Rolling Evo with arms
and power unit



Optional

**SEP.P + KIT.SE****KIT.SE**

Kit ruote
Wheels kit

**SEP.STR.05**

Kit pedane centrali
Kit central platforms

**SE.T**

Timone per
spostamento
Lift rudder

Caratteristiche tecniche | Technical features

	PESO / WEIGHT	600 kg		DISTANZA DI PRESA GRIP DISTANCE	da 650 a 3500 mm
	LARG. MAX / MAX WIDTH	2000 mm		POMPA / PUMP	300 bar
	LARG. MIN / MIN WIDTH	1007 mm		TAMPONE / BUFFER	60 mm
	ALT. MAX / MAX HEIGHT	1000 mm		IMBALLO / PACKAGING	2000x1200x1000 mm
	ALT. MIN / MIN HEIGHT	100 mm		PORTATA / CAPACITY	3000 kg 2500 kg (con rampe with ramps)